

The Ultimate Shield for Your Roof Deck.

US Roof Supply™ synthetic underlayment is a high-performance, multi-layer roofing protection system designed to replace traditional asphalt felt. Engineered with advanced polymer construction, it provides a lay-flat, water-shedding surface that stays intact under high winds and harsh UV exposure.



Anti-Slip Safety

Grip-Rite™ textured surface for superior traction in wet/dry conditions.

UV Resistant

Stabilized for up to 180 days exposure without drying or cracking.

Fast Install

25x stronger than felt but 5x lighter. More coverage, less weight.

All-Weather

Remains flexible from -40°F to 240°F. No cold cracking.

TECHNICAL SPECIFICATIONS (ASTM D8257)

PROPERTY	TEST METHOD	PERFORMANCE STANDARD	US ROOF SUPPLY RESULT
Tear Strength	ASTM D4533	> 20 lbs (MD/CD)	Pass / High Strength
Tensile Strength	ASTM D5034	> 40 lbs (MD/CD)	Exceeds Standard
Liquid Water Transmission	ASTM D4869	Pass	Pass (Impermeable)
Pliability (Cold Bend)	ASTM D226	No Cracking at -20°F	Pass (-40°F Safe)
Fire Rating	ASTM E108	Class A	Class A Fire Rated

PACKAGING & SHIPPING

Roll Dimensions **48" x 250' (10 Squares)**

Weight per Roll **~24 lbs (Lightweight)**

Rolls per Pallet **49 Rolls (Standard)**

Pallet Weight **~1,250 lbs**

Core Type **3" Heavy Duty Core**



US ROOF SUPPLY | 📞 (+86)13410006763 | ✉️ sales@usroofsupply.com | 🌐 www.usroofsupply.com

Disclaimer: All values are typical data and subject to normal manufacturing variations. Meets or exceeds ASTM D8257, D226 Type I & II.